

PLUVIAL CUBE HEAVY DUTY MODULE – DATA SHEET

Pluvial Cube Module Dimensions* (mm)	Module Configuration	Units per m ³	Module Volume (m ³)	Storage Volume (m ³)
500 (L) x 500 (W) x 550 (D)	Single	7.27	0.1375	0.132
500 (L) x 500 (W) x 1075 (D)	Double	3.72	0.2688	0.258
500 (L) x 500 (W) x 1600 (D)	Triple	2.5	0.4	0.384

* Bespoke modules with different configuration available



Single Module



Double Module



Triple Module

Product Data	Heavy Duty Pluvial Cube Module
Application	Stormwater Management
Average Weight (kg) – single module	8
Compressive Strength* (kN/m ²)	400
Lateral Strength* (kN/m ²)	200
Long Term Creep Testing** (kN/m ²)	200
Void Ratio (%)	96
Surface Void Ratio (%)	Greater than 90
Minimum Backfill Cover# (mm)	450
Maximum Backfill Cover (mm)	5000
Material	Polypropylene
Chemical resistance	Good
Bacterial Resistance	Good
UV Resistance	Good

Note: Other Modules with Compressive Strength more than 1500 kN/m² available

* Modules tested using UKAS calibrated test machine, range 0 – 60 Tons, UDL, loading rate 0.2 kN/m²

** Modules tested for long term creep testing for 90, 180 days and new ongoing test for 208 days.

Any cover less than 450 mm – contact ESS design department

Note: All Alderburgh products are manufactured to the highest quality, being subjected to rigid quality control. However the company cannot control conditions of application and use of its products, thus any warranty, written or implied, is given in good faith for materials only. Alderburgh Ltd will not accept any responsibility for damage or injury arising from storage handling, misapplication or misuse of its products. All transactions are subject to our standard condition of sales, copies of which are available on request. Product design and specification are subject to change without further notice

Solutions House, Dane St.
 Rochdale,
 OL11 4EZ,
 Tel: 01706 374416
 Fax: 01706 376785
 Email: sales@alderburgh.com



ENVIRONMENTAL SUSTAINABLE SOLUTIONS LTD